



Wiremold
10AT Prewired Evolution™ Series Poke Thru Device, Surface Style Cover
Part No. 10ATCPBK



Proof that bigger and better go hand in hand: Evolution Series 10inch Poke-Thru Devices offer more capacity, flexibility and versatility than any other poke-thru device on the market. Featuring eight-gangs of capacity, redesigned and easier to use covers, recessed connections below floor level, and enough internal wiring capacity to eliminate the need for a junction box. Evolution Series 10inch Poke-Thru Devices are ready to meet the marketinchs increased demand for more power, more A/V, and more communications.

Features & Benefits

For use with 10" (254mm) diameter hole. Cover and stem are pre-assembled together. All devices are recessed 4 1/2" (114mm) below the finished floor level. Unit ships complete with an all aluminum cover (assembled) designed to sit on top of finished floor surface (carpet, tile, wood, concrete or terrazzo). Powder coated black finish.

Specifications

General Info

Product Line	Wiremold	Color	Black
UPC Number	786564087090	Country Of Origin	United States

Application Sector	Commercial	Standard	cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT, cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY Meets Article 300.21 300.22[C] &314 of NEC
--------------------	------------	----------	--

Type	Poke-Thru
------	-----------

Dimensions

Product Width US	11.25 in	Product Weight US	20.87 lb
Product Volume US	1407.38 cu in	Product Depth US	11.12 in
Product Height US	11.25 in	Cubic Capacity	14 cu in

Core Hole Size	10 in
----------------	-------

Listing Agencies / 3rd Party Agencies

cULus ListingNumber	E2961	cULus Listed	Yes
---------------------	-------	--------------	-----

Buy American Act Compliance

NAFTA	Yes
-------	-----

Additional Information

RoHS Conformant	Yes	Product Environmental Profile	Yes
-----------------	-----	-------------------------------	-----

Technical Information

Cable Entry	Conduit Stubs & Pass Through	Number of Outlets	4
-------------	------------------------------	-------------------	---
