



**Pass and Seymour**  
**15A, 125V Watertight Straight Blade Plug, Yellow**  
Part No. 14W47



Rated watertight for 1,500 psi high-pressure hosedown, Pass and Seymour plugs and connectors feature multiple seals to ensure protection against the environment. Constructed of a sturdy rubber body, which makes them impact- and chemical-resistant, they have nickel-plated blades and contacts for superior corrosion resistance.

## Features & Benefits

Thermoplastic elastomer (TPV) construction stands up to impacts, oils, chemicals, heat and weather.

Devices resist high-pressure hose down of 1,500 psi.

Large ribs on body for a superior grip when mating.

Nickel-plated blades and contacts for long-lasting, superior corrosion resistance.

Color-coded sealing bushings provided for a large range of cord diameters.

For covering patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

## Specifications

### General Info

|                   |                |                    |            |
|-------------------|----------------|--------------------|------------|
| Product Line      | Pass & Seymour | Color              | Yellow     |
| Country Of Origin | United States  | Application Sector | Industrial |
| Standard          | UL498          | Type               | Plug Tail  |

### Dimensions

|                  |         |                  |         |
|------------------|---------|------------------|---------|
| Product Width US | 1.85 in | Product Depth US | 2.62 in |
|------------------|---------|------------------|---------|

### Listing Agencies / 3rd Party Agencies

|            |     |                 |        |
|------------|-----|-----------------|--------|
| CSA Listed | Yes | CSA File Number | 701645 |
|------------|-----|-----------------|--------|

### Technical Information

|                 |   |          |      |
|-----------------|---|----------|------|
| Number of Wires | 3 | Amperage | 15 A |
|-----------------|---|----------|------|

---

Number of Poles

Double Pole

Wire Size

14 - 0 AWG

---

Voltage

125.0 V

---