

## radiant Collection radiant® Tamper-Resistant 20A Duplex Self-Test GFCI Receptacles with SafeLock® Protection and Night Light, Ivory Part No. 2097NTLTRI



Ideal for replacing outlets by kitchen or bathroom sinks, this combination device from the radiant® Collection includes a tamper-resistant GFCI outlet paired with a sealed, built-in LED light which automatically turns on in the dark for easier nighttime navigation. Designed for safety, this self-testing GFCI outlet complies with National Electrical Code and makes trips easier to recognize and fix than GFCI breaker alternatives, thanks to accessible indicator light and reset button right on the outlet. 20A outlets are ideal for use with larger appliances, as well as to meet regional requirements (Chicago, Canada). Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately.

## Features & Benefits

Replaces any standard outlet with ease, in as little as 10 minutes.

Protects against shock caused by ground-fault occurrences. Unlike breaker alternatives, GFCI outlets make it easier to fix trips with a convenient reset button on the outlet.

Hidden sensor controls night light based on ambient light, automatically Features durable, high-impact resistant thermoplastic construction. turning on when it is dark.

Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisishutters" for an invisible effect.

More color options available to fit any style.

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.

## **Specifications**

## General Info Product Line Pass & Seymour Replaced by Part Number Color Country Of Origin China Ivory Number of Receptacles 2 Features Nightlight GFCI, Indoor, Residential, Self-Test, Outlet Type Residential/Commercial **Application Sector** Tamper-Resistant Standard cULus, UL Listed, FSUL Warranty Type 1-Year Limited Warranty Outlet Type **Dimensions** Product Width US 1.73 in Product Depth US 1.03 in 4.2 in Product Height US

Listing Agencies / 3rd Party Agencies			
cULus Listed	Yes		
Technical Information			
Interrupt Rating	4 A	Frequency Rating	60 Hz
Trip Range	5±1 mA	Connection	Back and Side Wire
Number of Gangs	1	Amperage	20 A
Number of Poles	Double Pole	Indoor/Outdoor	Indoor
Mounting Type	Вох	Voltage	125.0 V
Environmental Conditions	95% Humidity, UL 94 V2		