

### radiant Collection radiant® Tamper-Resistant 20A Duplex Self-Test GFCI Receptacle with SafeLock® Protection, Light Almond Part No. 2097TRLA



GFCI receptacles from the radiant® Collection self-test automatically every three seconds to ensure reliable protection from shock due to ground fault occurrences. Meeting National Electrical Code requirements for ground fault protection, GFCI receptacles make it easier to recognize and fix trips right where they happen - no more confusion at the breaker box. 20A outlets are ideal for use with larger appliances and in commercial settings, as well as to meet regional requirements (Chicago, Canada). GFCI protection is required by code in bathrooms, kitchens, garages, basements, outdoor areas, and for any other outlets found within six feet of a sink or water source. GFCI outlets should always be used when replacing existing GFCI outlets during renovation. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately. Spec-Grade devices are engineered to meet federal specifications for use in commercial installations.

downstream outlets if wired incorrectly.

replaced.

minutes.

Conducts an industry-leading automatic self-test every 3 seconds. If

Extends GFCI protection to "downstream" outlets when used with

Replaces any standard receptacle with ease, in as little as 10

More color options available to fit any style, including finishes to

# Features & Benefits

Protects against shock caused by ground-fault occurrences. Unlike breaker alternatives, GFCI receptacles make it easier to fix trips with a the device ever fails, the indicator light flashes to signal it should be reset button right on the device.

Equipped with proven SafeLock protection feature: if critical components are damaged and protection is lost, power to the outlet is feed-thru wiring configuration. Note: Will cut power to face and disconnected.

Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect.

Features durable, high-impact resistant thermoplastic construction.

match current hardware and lighting trends.

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the 10kA short circuit rating radiant® Collection.

20 Amp feed-thru capacity

### **Specifications**

# General Info

| Product Line      | Pass & Seymour  | Replaced by Part Number |                         |
|-------------------|---|-------------------------|-------------------------|
| Color             | Light Almond  | Finish                  | Matte                   |
| Country Of Origin | China   | Number of Receptacles   | 2                       |
| Outlet Type       | GFCI, Indoor, Residential, Self-Test,<br>Tamper-Resistant | Application Sector      | Residential/Commercial  |
| Standard          | cULus, UL Listed, FSUL                                    | Warranty Type           | 1-Year Limited Warranty |
| Туре              | Outlet  |                         |                         |

#### **Dimensions**

| Product Width US                      | 1.73 in                | Product Depth US        | 1.13 in     |  |
|---------------------------------------|------------------------|-------------------------|-------------|--|
| Product Height US                     | 4.2 in                 |                         |             |  |
| Listing Agencies / 3rd Party Agencies |                        |                         |             |  |
| cULus Listed                          | Yes                    |                         |             |  |
| Additional Information                |                        |                         |             |  |
| Product Environmental Profile         | Yes                    |                         |             |  |
| Technical Information                 |                        |                         |             |  |
| Interrupt Rating                      | 4 A                    | Frequency Rating        | 60 Hz       |  |
| Trip Range                            | 5±1 mA                 | Number of Gangs         | 1           |  |
| Amperage                              | 20 A                   | Number of Poles         | Double Pole |  |
| Indoor/Outdoor                        | Indoor                 | NEMA Configuration Code | 5-20R       |  |
| Mounting Type                         | Вох                    | Voltage                 | 125.0 V     |  |
| Environmental Conditions              | 95% Humidity, UL 94 V2 |                         |             |  |