

## Wiremold 4AT Recessed Unwired Poke-Thru Stem Assembly

Part No. 4STC



Designed for retrofit and new construction, Evolution Series 4"
Poke-Thru devices provide convenient access to power,
communications, and audio/video services recessed below floor level
- providing maximum device protection. 2-gangs of capacity allow
you to configure services for the needs of your space. Evolution
Series 4" Poke-Thru devices are the perfect fit for kiosks, training
rooms, classrooms, healthcare facilities or commercial buildings
with open-space architecture.

## Features & Benefits

Designed for retrofit and new construction, Evolution Series 4" Poke-Thru devices provide convenient access to power, communications, and audio/video services recessed below floor level - providing maximum device protection. 2-gangs of capacity allow you to configure services for the needs of your space. Evolution Series 4" Poke-Thru devices are the perfect fit for kiosks, training rooms, classrooms, healthcare facilities or commercial buildings with open-space architecture.

Recessed Devices: All power, communications and A/V devices are recessed below floor level, providing maximum protection and device longevity.

Unique Cover Design: The cover opens a full 180 degrees with sliding doors to keep wires, connections and people safe.

6 Finishes: Evolution Series Poke-Thru Devices are available in six finishes to seamlessly match your environment.

Open System for Expanded Compatibility: Accepts industry standard power, communications Seymour® Wireless RF and A/V devices from most manufacturers including Legrand AVIP, Extron® and more. receptacles to control p

Plug Load Control up to 30
Feet: Tested with Pass &
Seymour® Wireless RF
receptacles to control plug
loads up to a distance of 30 feet
when the cover is closed.

2 Hour Fire Rating: Evolution Series Poke-Thru Devices use an intumescent material that maintains the fire rating of any floor for up to 2 hours.

## Specifications

## General Info

Product Line	Wiremold	UPC Number	786564090915
Country Of Origin	United States	Construction	Assembled
Number of Knockouts	10	Application Sector	Commercial

cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT. cULus Listed Nonmetallic Outlet Boxes and Fittings Classified for Fire Resistance: Standard Туре Poke-Thru File R8209 Guide CEYY. Meets Article 300.21 300.22[C] and 314 of NEC. Dimensions Product Width US 4.75 in Product Height US 18.562 in Cubic Capacity 24.5 cu in Listing Agencies / 3rd Party Agencies cULus ListingNumber E2961 cULus Listed Yes Buy American Act Compliance NAFTA Yes Additional Information RoHS Conformant Yes Technical Information

1 1/2 in trade size conduit for data, 3/4 in trade size

conduit for power,.75 in

Number of Outlets

0

Cable Entry