

Wiremold Omnibox® Series Single Gang Cast Iron Floor Box

Part No. 880CS1-1



The 880CS1-1 single gang Omnibox® Floor Box provides an excellent activation solution for applications where single service is required in open space areas. The 880CS1-1 floor box is offered in a durable cast iron construction, designed to be installed in on-grade concrete floor applications and to meet a wide range of market requirements.

This floor box series has many applications, some of which are schools, financial institutions, and commercial office buildings.

Features & Benefits

TopGuard protection. All cover assemblies for the Omnibox Floor Box Series have TopGuard protection. An integral design which keeps out water, dirt, and debris from the power and communication compartments.

Fully adjustable box. Before and after concrete pour adjustability. Lower installed cost.

Watertight cast-iron construction. Meets requirements for on grade or below grade application Three-gang configurations, maximum flexibility. Can remove divider for greater capacity. Supports multiservice applications.

Boxes and covers have been listed by Underwriters Laboratories Inc. to their standard UL514A, 514C, 514D, and Canadian standard C22.2

Flush activation assemblies for carpet and tile. Aesthetically pleasing assemblies are steel.

Datacom connectivity options. Accepts industry standard and proprietary devices from a wide range of manufacturers to provide a seamless and aesthetically pleasing interface for voice, data, audio, and video applications interchangeable for both cast-iron and stamped at the point-of-use. A wide selection of data and bezel options available for use with Ortronics TracJack and Series II devices.

Specifications

General Info			
Product Line	Wiremold	Color	Silver
UPC Number	786564515876	Country Of Origin	China
Construction	Assembled	Number of Knockouts	1
Application Sector	Commercial	Standard	cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT. Meets Article 314.27(C) of NEC.

Туре	Floor Box			
Dimensions				
Product Width US	4.5 in	Product Weight US	6.63 lb	
Product Volume US	104.34 cu in	Product Depth US	6.63 in	
Product Height US	3.5 in	Cubic Capacity	48 cu in	
Listing Agencies / 3rd Party Agencies				
cULus ListingNumber	E2961	cULus Listed	Yes	
Additional Information				
RoHS Conformant	Yes	Product Environmental Profile	Yes	
Technical Information				
Cable Entry	Conduit Threads	Number of Outlets	0	