

adorne Collection adorne® 15A Two-Gang Pop-Out Outlet, Magnesium Part No. ARPTR152GM2

The cleverest way to add power and style, the Pop-Out Outlet extends to offer 3-plug access, then uniquely disappears back into the wall with a simple push when not in use. Made exclusively for use with screwless Wall Plates from the adorne® Collection, sold separately.



Features & Benefits

For complete installation, device must be paired with an adorne® screwless Wall Plate (not included). Available in a range of contemporary colors and stunning finishes.	Perfect anywhere you'd like to hide outlets when not in use, for added style and safety.
Provides additional power with 3-plug access when extended from wall.	Disappears back into the wall with a simple push when not needed.
Installs easily in as little as 15 minutes.	Comes with a special frame for mounting and requires a deep electrical outlet (22.5 cubic inches). No new wires required for typical installation.
Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-schutters" for an invisible effect	More color options available to fit any style, including finishes to match current hardware and lighting trends.

Specifications

"invisi-shutters" for an invisible effect.

General Info

Product Line	Pass & Seymour	Replaced by Part Number	
Color	Magnesium	Finish	Frosted
Country Of Origin	China	Number of Receptacles	3
Features	Pop-Out	Outlet Type	Indoor, Pop-Out, Residential, Tamper- Resistant
Application Sector	Residential	Standard	CULUS
Warranty Type	Limited Lifetime Warranty	Туре	Outlet

Dimensions

Product Width US	4.8 in	Product Depth US	2.6 in			
Product Height US	4.7 in					
Listing Agencies / 3rd Party Agencies						
cULus Listed	Yes					

Technical Information

Phase	Single	Connection	Side and Back Wire
Number of Wires	3	Number of Gangs	1
Amperage	15 A	Number of Poles	Double Pole
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor
NEMA Configuration Code	5-15R	Mounting Type	Box
Voltage	125.0 V	Connection Type	Internal Pressure Plates
Environmental Conditions	95% (relative humidity, non- condensing)		