


adorne Collection adorne® 15A Single Tamper-Resistant Outlet, White Part No. ARTR151W10



Designed with the same commitment to style and safety as the entire adorne Collection, this device is ideal as a dedicated outlet for large or stationary appliances, or in small or narrow areas where a single plug is needed. The single outlet features "invisi-shutters" for discreet tamper-resistance that keeps children safe without compromising on style.

Made exclusively for use with screwless Wall Plates from the adorne® Collection, sold separately.

Features & Benefits

For complete installation, device must be paired with an adorne® screwless Wall Plate (not included). Available in a range of contemporary colors and stunning finishes.

Replaces a standard outlet with ease in as little as 10 minutes.

Creates a designated outlet, ideal for use with appliances or products and devices with larger plugs.

Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect.

More color options available to fit any style, including finishes to match current hardware and lighting trends.

Specifications

General Info			
Product Line	Pass & Seymour	Color	White
Finish	Matte	Country Of Origin	China
Number of Receptacles	1	Outlet Type	Indoor, Residential, Tamper- Resistant
Application Sector	Residential/Commercial	Standard	RoHS, CSA, cULus, UL, Conforms to NEMA WD-1 and WD-6
Warranty Type	Limited Lifetime Warranty	Туре	Single, Tamper-Resistant
Dimensions			
Product Length US	1.33 in		

Listing Agencies / 3rd Party Agencies					
CSA Listed	Yes	cULus Listed	Yes		
CSA File Number	C22.2 No.42				
Additional Information					
RoHS Conformant	Yes				
Technical Information					
Connection	Wired	Amperage	15 A		
Current Rating	15 A	Indoor/Outdoor	Indoor		
Wattage	1875 W	NEMA Configuration Code	5-15R		
Mounting Type	Вох	Operating Temperature	86°F		
Voltage	125.0 V	Connection Type	Internal Pressure Plates		
Environmental Conditions	Flammability Rating: UL 94 V2				