

## Wiremold PLGMD SGL CRCT 12IN. OC 6FT. NM2400

Part No. NM24GB612



Plugmold® Multioutlet Systems are available in a wide variety of lengths and fittings and in a variety of finishes to provide versatile solutions for many applications. Plugmold options include single or alternating circuits, standard or isolated ground receptacles, GFCI protection, tamper-resistant protection, USB charging, Snapicoil® harnesses of prewired receptacles, and cord-ended units. Plugmold® Multioutlet Systems are available in black or ivory ScuffCoat™ finish, painted white or gray enamel steel, stylish stainless steel, anodized aluminum and durable textured ivory nonmetallic. The painted steel product works with many types of decor and is paintable to integrate with most color schemes. Durable stainless steel and anodized aluminum Plugmold products are corrosion-resistant, making them ideal for labs.

## Features & Benefits

6' (1.8m) length with 12" (305mm) receptacle spacing. 20A receptacles. 3-wire, #12 THHN (1 hot, 1 neutral, and insulated ground conductor). Packed 2 per carton. Each unit supplied with two (2) Blank End Fittings.

## Specifications

Genera	П	nfo
Ociici a	L I	1110

Product Line	Wiremold	UPC Number	786776520194
Country Of Origin	United States	Number of Receptacles	6
Application Sector	Commercial	Standard	cULus Listed Base & Blank Cover: File E90378 Guide RJBT. Multioutlet Assemblies: File E15191 Guide PVGT. Fittings: File E90377 GuideRJPR. Base & Blank Cover & Plugmold Series w/Snapcoil Harness: Meets Article 386 of NEC. Meets Section 12-3032 of CEC. Plugmold Wired Sections: Meets Article 380 of NEC. Meets Section 12-3032 of CEC.
Туре	Plugmold		
Dimensions			
Product Width US	1.75 in	Product Depth US	1.0 in

Product Length US	1.75 in				
Listing Agencies / 3rd Party Agencies					
cULus ListingNumber	E15191	cULus Listed	Yes		
Buy American Act Compliance					
NAFTA	Yes				
Additional Information					
RoHS Conformant	Yes				
Technical Information					
Amperage	15 A	Enclosure Type	Non-Metallic		
Voltage	120.0 V	Environmental Conditions	Dry interior locations		