



Part No. P642664



The aluminum I-beam design of ITray is perfect for industrial installations with large diameter cables in long span situations, minimizing total tray width and creating a smooth transition between straight sections and fittings. A structural offset in the sidewall creates strong, mid-span splices that need fewer supports. Each splice snaps in place and stays without holding, Additionally, only four bolts are needed for each splice reducing hardware needs by 50%. These features allow Itray to be installed up to 30% faster than standard tray.



## Features & Benefits

Material: (.052") HDPE

Flame Class per UL 94 V-0

Tempature Range: -100 to 160 deg F

Quantity: 1

Use with: 1893 Hold-down Clamp/Guide

**UV** Resistant

RoHS Compliant

Color: Red

Construction: Blanked & Corrugated for

## Specifications

General Info

| Product Line | Cablofil     | Finish            | АТ     |
|--------------|--------------|-------------------|--------|
| UPC Number   | 800388247482 | Country Of Origin | Mexico |
| Dimensions   |              |                   |        |

| Product Width US  | 2.75 in     | Product Weight US | 0.031 lb |
|-------------------|-------------|-------------------|----------|
| Product Volume US | 0.005 cu ft | Product Depth US  | 6.474 in |
| Product Height US | 0.52 in     |                   |          |

## Buy American Act Compliance

BAA Yes