



Straight Blade Connector 2-Pole 3-Wire 20A 125A

Features & Benefits

- Unit arrives completely ready-to-wire, cuts installation time significantly.
 - Nylon housing provides impact and chemical resistance. Rugged two-piece cord grip provides more uniform cord retention. Internal dust shield keeps terminals free of contaminants.
 - Tri-drive assembly screws are standard on all Specification Grade plugs and connectors.
 - All 3-wire terminals located on the same plane, allows for quick wire termination from any angle.
 - Heavy-duty brass alloy blades and contacts, resist heat rise, provide excellent conductivity.
 - Cord-grip screws recessed to protect installer against screwdriver head slippage.
- For covering patents, see www.legrand.us/patents.

Specifications

General Info

| | | | |
|-------------------|----------------|----------|--------|
| Product Line | Pass & Seymour | Color | Black |
| Country Of Origin | Mexico | Standard | UL 498 |
| Type | Straight Blade | | |

Dimensions

| | | | |
|------------------|----------|-------------------|----------|
| Product Width US | 1.516 in | Product Length US | 2.638 in |
|------------------|----------|-------------------|----------|

Listing Agencies / 3rd Party Agencies

| | |
|--------------|-----|
| cULus Listed | Yes |
|--------------|-----|

Additional Information

| | |
|-------------------------------|-----|
| Product Environmental Profile | Yes |
|-------------------------------|-----|

Technical Information

| | | | |
|------------|----------------|-----------------|-------------|
| Connection | Wire Grounding | Number of Wires | 3 |
| Amperage | 20 A | Number of Poles | Double Pole |
| Wire Size | 4 | Voltage | 125.0 V |
