

## Pass and Seymour 15A, 250V EHU GCM Plug, Black and White

Part No. PS5666XGCM



Straight Blade GCM PLUG 3W 15A 250V

### Features & Benefits

Integral indication of ground continuity and power status. Continuous monitoring enhances personnel safety and adds convenience.

Chemical- and impact-resistant nylon housing features horizontal, easy-grip ribs on back body.

Internal dust shield keeps terminals free of contaminants.

Color-coded terminal screws are positioned on the same plane and backed-out for fast installation.

For covering patents, see www.legrand.us/patents.

Dual, bright LED indicators with 360 degree visibility. Green LEDs indicate proper ground continuity and power status. Red LEDs indicate ground continuity loss or reversed polarity. No LED indicates open hot, open neutral, or hot to ground cross. For 250V configurations: Hot to ground cross will be indicated by a green and red LED.

Exclusive two-piece cord grip accepts a wide range of cord widths. Provides more consistent pressure for superior conductor retention.

Recessed cord-grip screw reduces screwdriver slippage, improves safety. Quick-thread tri-drive assembly and cord-grip screws come backed-out and ready-to-wire.

Industrial-strength, brass alloy plug blades and connector contacts resist heat rise, provide excellent conductivity.

Add an EHU15AN for angled applications.

# Specifications

### General Info

Product Line	Pass & Seymour	Color	Black
Country Of Origin	Mexico	Application Sector	Residential/Commercial
Standard	UL498	Туре	Plug Tail

#### Dimensions

Product Width US	1.516 in	Product Length US	1.752 in

Listing Agencies / 3rd Party Agencies						
cULus Listed	Yes					
Technical Informat	ion					
Phase	Three	Number of Wires	3			
Amperage	15 A	Number of Poles	Double Pole			
Wire Size	18 - 12 AWG	Voltage	250.0 V			