



**Wiremold**  
**RC4 Multi-Service Poke-Thru Assembly, Aluminum**  
Part No. RC4ATCAL



Unit includes four prewired 20A receptacles. Each duplex receptacle is wired as separate circuit. The duplex can be wired as a standard receptacle or isolated ground. Finish flange available in gray (GY), black (BK), ivory (VY) or brushed metal finishes in aluminum (AL), and brass (BS). Aluminum and brass flanges shipped with black slide cover. Brass flange also available with nonmetallic brass colored slide holder (AB). Aluminum flange also available with nonmetallic aluminum colored slide holder (AA). Includes Wiremold Open System unloaded adapters to accept four discrete keystone connectors from most manufacturers. Unit also includes Ortronics TracJack Mounting adapters and Ortronics Series II Communication Housing. Modular jacks sold separately. NOTE: Assembled with scrub water gasket. For use on tile or carpet floors. RC4 Series Poke-Thru Devices require a 4inch (102mm) diameter hole. Not designed to work with bare concrete or terrazzo. Floor covering thickness 1/8inch minimum.

## Features & Benefits

Unit includes four prewired 20A receptacles. Each duplex receptacle is wired as separate circuit. The duplex can be wired as a standard receptacle or isolated ground. Finish flange available in gray (GY), black (BK), ivory (VY) or brushed metal finishes in aluminum (AL), and brass (BS). Aluminum and brass flanges shipped with black slide cover. Brass flange also available with nonmetallic brass colored slide holder (AB). Aluminum flange also available with nonmetallic aluminum colored slide holder (AA). Includes Wiremold Open System unloaded adapters to accept four discrete keystone connectors from most manufacturers. Unit also includes Ortronics TracJack Mounting adapters and Ortronics Series II Communication Housing. Modular jacks sold separately. NOTE: Assembled with scrub water gasket. For use on tile or carpet floors. RC4 Series Poke-Thru Devices require a 4inch (102mm) diameter hole. Not designed to work with bare concrete or terrazzo. Floor covering thickness 1/8inch minimum.

## Specifications

### General Info

|                     |  |                    |            |
|---------------------|--|--------------------|------------|
| Product Line        | Wiremold   | Color              | Aluminum   |
| UPC Number          | 786564131526   | Country Of Origin  | Mexico     |
| Number of Knockouts | 2  | Application Sector | Commercial |
| Standard            | cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT, cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY Meets Article 300.21 300.22[C] &314 of NEC | Type               | Poke-Thru  |

### Dimensions

|                  |         |                   |         |
|------------------|---------|-------------------|---------|
| Product Width US | 8.25 in | Product Weight US | 5.67 lb |
|------------------|---------|-------------------|---------|

---

|                   |               |                  |          |
|-------------------|---------------|------------------|----------|
| Product Volume US | 1114.86 cu in | Product Depth US | 16.38 in |
|-------------------|---------------|------------------|----------|

---

|                   |         |                |            |
|-------------------|---------|----------------|------------|
| Product Height US | 8.25 in | Cubic Capacity | 24.5 cu in |
|-------------------|---------|----------------|------------|

---

|                |      |
|----------------|------|
| Core Hole Size | 4 in |
|----------------|------|

---

### Listing Agencies / 3rd Party Agencies

---

|                     |       |              |     |
|---------------------|-------|--------------|-----|
| cULus ListingNumber | E2961 | cULus Listed | Yes |
|---------------------|-------|--------------|-----|

---

### Buy American Act Compliance

---

|       |     |
|-------|-----|
| NAFTA | Yes |
|-------|-----|

---

### Additional Information

---

|                 |     |                               |     |
|-----------------|-----|-------------------------------|-----|
| RoHS Conformant | Yes | Product Environmental Profile | Yes |
|-----------------|-----|-------------------------------|-----|

---

### Technical Information

---

|             |                           |                   |   |
|-------------|---------------------------|-------------------|---|
| Cable Entry | Knockouts & Conduit Stubs | Number of Outlets | 4 |
|-------------|---------------------------|-------------------|---|

---