

radiant Collection radiant® Single-Pole 3-Way Vacancy Sensor, Tri-Color

Part No. RRW600VTC



Never worry about leaving the lights on, with the radiant Registered Vacancy Sensor. It automatically shuts off when a room is empty, and includes an adjustable delay setting of up to 20 minutes to match your needs. Designed for ease and style, it features a built-in locator light, and the sleek, clean lines of radiant Registered for a sophisticated touch. Made exclusively for use with screwless Wall Plates from the radiant Registered Collection, sold separately.

Features & Benefits

Works with various lights/bulbs, including: Incandescent, LED, fluorescent, compact fluorescent (CFL), magnetic low-voltage (MLV) and electronic low-voltage (ELV), 1/6 hp.

Turn the light on when you enter, and let it turn itself off automatically after you leave for true convenience.

Features an adjustable time delay, letting you set the automatic shut-off after a specified window of time. Delay settings range from 30 seconds to 20 minutes after the room is vacated.

Installs easily in place of a standard light or fan (single-pole) switch. No neutral wire required.

Locator light illuminates when switch is off, emitting a soft glow to help you find it in the dark.

More color options available to fit any style, including finishes to match current hardware and lighting trends.

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection.

The secret for always turning the lights off? A device that does it for you automatically. Perfect for bathrooms, hallways, closets, and garages.

Specifications

General Info					
Product Line	Pass & Seymour	Color	Ivory, Light Almond, White		
Country Of Origin	China	Features	Motion Sensor		
Switch Type	Motion Sensor	Application Sector	Residential		
Standard	cULus				
Dimensions					
Product Width US	1.69 in	Product Depth US	1.88 in		

Product Height US	2.63 in				
Listing Agencies / 3rd Party Agencies					
cULus Listed	Yes				
Technical Information					
Target Size	180 deg	Response Frequency	60 Hz		
Sensor Type	Occupancy	Amperage	5 A		
Number of Poles	Single Pole	Wattage	600 W		
Mounting Type	Вох	Sensing Range	600 sq ft		
Sensitivity	60Hz	Load	120VAC		
Environmental Conditions	Indoor Use Only				