

radiant Collection radiant® Single-Pole 3-Way Vacancy Sensor, White

Part No. RRW600VW



Never worry about leaving the lights on, with the radiant® Vacancy Sensor. It automatically shuts off when a room is empty, and includes an adjustable delay setting of up to 20 minutes to match your needs. Designed for ease and style, it features a built-in locator light, and the sleek, clean lines of radiant® for a sophisticated touch. Made exclusively for use with screwless Wall Plates from the radiant® Collection, sold separately.

Features & Benefits

Passive infrared (PIR) sensor switch technology with 180° coverage up to 600 sq. ft. Rated for up to 600W (5A) of LED lighting.

Turn the light on when you enter, and let it turn itself off automatically after you leave for true convenience. Perfect for bathrooms, hallways, closets, garages, and more.

Features an adjustable time delay to off after no motion is detected. Delay settings range from 30 seconds to 20 minutes requirements for automatic off lighting control. after the room is vacated (default 20 minute delay).

Replace any basic light or fan switch in 15 minutes or less. Supports single pole and multi-location installs. No neutral required.

More color options available to fit any style, including finishes to match current hardware and lighting trends.

Works with virtually any bulb/fixture, including: LED, incandescent, fluorescent, compact fluorescent (CFL), magnetic low-voltage (MLV) and electronic low-voltage (ELV), 1/6 hp.

Locator light illuminates when switch is off, emitting a soft glow to help you find it in the dark.

Manual ON/Auto OFF functionality. Meets California Title 24

Complete the look with a sleek, screwless radiant® Wall Plate, and coordinate with other designer switches and outlets available from the radiant® Collection

Specifications

General Info Product Line Pass & Seymour Color White Features Country Of Origin China Motion Sensor Switch Type Motion Sensor **Application Sector** Residential Dimensions Product Width US 1.69 in Product Depth US 1.88 in

Product Height US	2.63 in		
Listing Agencies / 3rd Party Agencies			
cULus Listed	Yes		
Technical Information			
Target Size	180 deg	Response Frequency	60 Hz
Sensor Type	Vacancy	Amperage	5 A
Number of Poles	Single Pole 3-Way	Indoor/Outdoor	Indoor
Wattage	600 W	Mounting Type	Вох
Sensing Range	600 sq ft	Voltage	120 V
Sensitivity	60Hz	Load	120VAC