



Wiremold
Plug-In Outlet Center Unit / 120V/20A/8 O/L /lighted switch/15' cord
Part No. ULB820-15



Eight 20A, 120V, 60Hz, 2500 watt outlets, lighted switch, putty white aluminum housing, 15' (4.6m) 12/3 SJT black cord with NEMA5-20 plug. Length 17 1/4" (438mm). Receptacle center-to-center 1 1/2" (38mm). Snap-on slide-off mounting.

Features & Benefits

Eight 20A, 120V, 60Hz, 2500 watt outlets, lighted switch, putty white aluminum housing, 15' (4.6m) 12/3 SJT black cord with NEMA5-20 plug. Length 17 1/4" (438mm). Receptacle center-to-center 1 1/2" (38mm). Snap-on slide-off mounting.

Specifications

General Info

| | | | |
|-----------------------|--------------|--------------------|--------------|
| Product Line | Wiremold | UPC Number | 786776118339 |
| Country Of Origin | Mexico | Receptacle Type | Double |
| Number of Receptacles | 8 | Application Sector | Commercial |
| Standard | cULus Listed | Type | PIOC |

Dimensions

| | | | |
|------------------|--------|-------------------|-----------|
| Product Width US | 2.0 in | Product Length US | 17.063 in |
|------------------|--------|-------------------|-----------|

Listing Agencies / 3rd Party Agencies

| | | | |
|---------------------|--------|--------------|-----|
| cULus ListingNumber | E66421 | cULus Listed | Yes |
|---------------------|--------|--------------|-----|

Buy American Act Compliance

| | |
|-------|-----|
| NAFTA | Yes |
|-------|-----|

Additional Information

| | |
|-----------------|-----|
| RoHS Conformant | Yes |
|-----------------|-----|

Technical Information

| | | | |
|------------------|-------|----------|------|
| Frequency Rating | 60 Hz | Amperage | 20 A |
|------------------|-------|----------|------|

| | | | |
|---------------|--------------------|---------|---------|
| Mounting Type | Slide-off, Snap-on | Voltage | 120.0 V |
|---------------|--------------------|---------|---------|

| | |
|--------------------------|------------------------|
| Environmental Conditions | Dry interior locations |
|--------------------------|------------------------|
