

Wiremold 20GB506TRUSB 5' Plugmold® Multioutlet System with USB Part No. V20GB506TRUSB

Tamper-resistant receptacles. Tamper-Resistant, patented

Meets 2011 National Electrical Code® Tamper-Resistant

shutter system prevents improper insertion of foreign objects.

Compact design. Eliminates the need for bulky AC adapters.

5' Plugmold Multioutlet USB system



## Features & Benefits

USB charging. 2.4A USB type A receptacle charges faster than other USB receptacles and is compatible with USB 2.0 and 3.0 type devices.

Multiple colors and finishes. Painted finishes of black, gray, ivory, and white, as well as anodized aluminum and stainless steel versions integrate easily with any room decor.

This product meets the material restrictions of RoHS.

## Specifications

## General Info

Wiremold Product Line **UPC** Number 786776182637 Country Of Origin United States Number of Receptacles 9 cULus Listed Multioutlet assemblies: File E15191 Application Sector Standard Commercial Guide PVGT. Meets Article 380 of NEC. Plugmold Туре Dimensions 1.3 in 0.75 in Product Width US Product Depth US

requirements.

| Product Length US                     | 1.3 in                 |                               |         |
|---------------------------------------|------------------------|-------------------------------|---------|
| Listing Agencies / 3rd Party Agencies |                        |                               |         |
| cULus ListingNumber                   | E15191                 | cULus Listed                  | Yes     |
| Buy American Act Compliance           |                        |                               |         |
| NAFTA                                 | Yes                    |                               |         |
| Additional Information                |                        |                               |         |
| RoHS Conformant                       | Yes                    | Product Environmental Profile | Yes     |
| Technical Information                 |                        |                               |         |
| Frequency Rating                      | 60 Hz                  | Amperage                      | 20 A    |
| Enclosure Type                        | Steel                  | Voltage                       | 125.0 V |
| Environmental Conditions              | Dry interior locations |                               |         |
|                                       |                        |                               |         |